A 14	Approved For Release 2003/08/1 CONFIDENTIAL 004700360007-1	N
,	CLASSIFICATION SECRETA	B
COUNTRY	REPORT NO. 25X1	2 <u>5</u> >
торіс	Pumping Station in Faurei	
<u> </u>		
EVALUATIO		
DATE OF	CONTENT_To the end of 1948 25X1	
DATE OBTA	AINFD DATE PREPARED 27 March 1950	
REFERENC		
PAGES	25X1 ENCLOSURES (NO. & TYPE) 1 blueprint	
REMARKS.		
		25X
anne distribution, and hannes after some		Larring Contraction
5X1		
	1. Location:	
	The Faurei pumping station is in the vicinity of the Faurei railroad junction on the Euzau-Faurei-braila-Galatz railroad trunk line about 100 meters west of the Faurei railroad station.	
	2. luildings, layout, installations:	
	a. The pumping house is an old one-story brick building of 14 x 8 x 6 meters. Two piston pumps of the Worthington type with a pressure of 30 atmospheres, operating 200 m tons per 24 hours, are installed there. The two pumps are driven by an electric motor. They are auxiliary pumps for the Eaicoi-Cernavoda-Constanta trunk pipe line.	
	b. The workshop building, 14 x 6 x 6 meters, is an old one- story brickwork house about 15 meters west of the pump house. Pipe line repair work is done here and valves are reconditioned.	
	c. The boilerhouse, 14 x 8 x 4.5 meters (height of walls excluding roof), which was still under construction in the Fall of 1948, is about 200 meters east of the pump house. The brickwork was completed, but roof and equipment were lacking. Steam boilers for calefaction of the pipe line will be installed there. Calefaction is necessary as, in winter, Fauri is a critical section of the Ploesti-Cernavoda-Constanta pipe line. Previously, in mid-winter, the Luzau pumping station had to operate with an additional pressure of 20 atmospheres to press the oil which became viscous in the cold, through the pipe. This heating installation was constructed on order of the Soviets.	
5V1	d. A refinery is under construction 15 meters east of the boilerhouse. The brickwork of the brick building was completed but the roof was still missing in the Fall of 1948.	
5X1	stock in Ploesti.	
	e. The tanks of the station are arranged in two groups. One consists of four, 1,000-cu.m. tanks which are 20 meters apart CLASSIFICATION SECRET	25×
	This document is hereby regraded to ONFIDE Decement No. No Change In class No Change In class Declessified Declessified Archivist of the United States. Approved For Release 2003/08/11: CIA-RDP82-00-60-907 The Fr. Approved For Release 2003/08/11: CIA-RDP82-00-60-907	25 <u>X</u>

25X1

	Approved For Release 2003/08/11 : CIA-RDP82-00457R004700360007-1
25X1	SECRET/
	- 2 -
8	25X1
	between the pump house and the boilerhouse about 80 meters from the railroad linenother three-tank group is about 25 meters behind. These 2,000-cu.m. tanks are 25 meters apart. All tanks rest on concrete bases extending about 1 meter above ground.
	f. The loading platform, about 150 meters long, parallels the railroad line at a 5-meter distance. Ten railroad tank cars can be loaded at the same time (see Annex).
	Another minor pipe, about 2.5 cm in diameter, through which steam is to circulate, was projected as pipe line heating system. The latter pipe is to be installed within the former one.
25X1	Comment:
	The pump station described by this report belongs to the Baicoi-Ruzau-Cernavoda-Constanta pipe line*. It is about 130 km from Laicoi, the starting point of the pipe line, and 170 km from Constanta, the terminal of the pipe line. Another pipe line branching off in Faure runs via Calati to the Doviet Danube port of Reni. This pipe line was constructed by Rumania after the war by order of the Soviets to deliver oil to the Soviet Union.
25V1	

1 Annex: Elueprint, Fumping Station in Faurei.

Approved For Release 2003/08/11 : CIA-RDP82-00457R004700360007-1